

Sioux's IW38TBP Series Drivers and Wrenches Deliver a Real Impact!



IW38TBP-3P

IW38TBP-2Q

Looking for an impact tool program that delivers? The Sioux Tools **IW38TBP** series gives you the speed, comfort and reliability you have grown to expect out of a Sioux quality built tool program. The **IW38TBP** impact wrench and driver are versatile enough to handle applications ranging from furniture, appliance and trailer manufacturing to manufactured housing.

Whether your application calls for wood screws, self-tapping metal screws or even lag bolts, the **IW38TBP** Series drives them home with the power and performance you expect from Sioux. The 4-level power control allows the operator to dial down the torque output for precise handling of smaller screws and fasteners. With a thumb operated reverse and an ergonomic comfort grip, the ease and comfort of this tool are second to none.

Available With 1/4" QC
or 3/8" SQ Drive

Contoured Trigger
For Comfort & Control

4 Level Power Control
Can be adjusted to fit
any application

Thumb-operated Reverse
For right or left hand operator



Comfort Grip
Protects operator from cold
and vibration

Down Handle Exhaust
Can be rotated 360° to direct
air away from operator



Impact Wrenches / Impact Drivers

Model Number	Drive Size		Bolt Cap. Grade 5		Working Torque Range ¹		Maximum Torque		Blows Per Minute	Free Speed rpm	Weight		Length		Side To Center		Avg Air Consump.		Socket Retainer Style
	in.	mm	in.	mm	ft lb	Nm	ft lb	Nm			lb	kg	in.	mm	in.	mm	cfm	l/s	
Pistol Grip																			
IW38TBP-3P	3/8	10	1/4	6	10-70	13-95	70	95	2000	8000	2.1	1.0	6.3	160	0.9	22	2	1	Pin
IW38TBP-2Q	1/4	6	1/4	6	10-70	13-95	70	95	2000	8000	2.1	1.0	6.3	160	0.9	22	2	1	QC

¹ Maximum working torque determined by 5 second rundown on appropriate Skidmore-Wilhelm Torque-Tension Tester.

General:

Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment:

Parts List • Safety and Instruction Manual

siouxtools.com



250 Snap-on Drive
P.O. Box 1596
Murphy, North Carolina USA 28906
PH: 828.835.9765
FAX: 828.835.9685
TOLL FREE: 866.259.7291
TOLL FREE FAX: 800.722.7236

Benelux
Tel.: (N) 31 (0) 20 568 26 64
(B) 32 (0) 14 23 19 67
Fax: (N) 31 (0) 20 568 26 60
(B) 31 (0) 14 23 26 27
e-mail: snap@snap-on.nl

Latin America
Tel.: 305-271-0944
Fax: 305-271-7152
e-mail: latinamerica.caribbean@snapon.com

Germany
Tel.: 49 2104 9509-0
Fax: 49 2104 9509-99
e-mail: snapon.industrial@snapon.com

Italy
Tel.: 00 39 02 66 04 53 70
Fax: 00 39 02 61 29 78 15
e-mail: indus.italia@snapon.com

United Kingdom
Tel.: 44 (0) 1536-413904
Fax: 44 (0) 1536-413874
e-mail: industrialuk@snapon.com

Asia
Tel.: 65-6451-5570
Fax: 65-6451-5574
email: esales.sg@snapon.com

Australia
Tel.: 61 2 9837 9100
Fax: 61 2 9624 2578
e-mail: SOTA.customerservice@snapon.com

Distributed By:

