

# SDG7 & SAG7 METAL BODY DIE GRINDER

S E R I E S



## Features SAG7 Series:

- Powerful 5 vane motor maintains speed under load
- Heavy duty double tapered collet
- Teasing throttle for maximum control
- Lever throttle with lock-off
- Ball bearing construction
- Heavy Duty spiral bevel gearing for durability and smooth operation
- Compact angle head allows access into tight spaces
- Grease zerk in gear case
- Adjustable speed control

## SDG7 Series Features:

- Powerful 5 vane motor maintains speed under load
- Heavy duty double tapered collet
- Teasing throttle for maximum control
- Lever throttle with lock-off
- Ball bearing construction
- Adjustable speed control



SDG7S25F



**Straight Die Grinders**

Model Number	Free Speed		Weight		Length		Sound Level	Air Consumption		Collet Size	Exhaust
	rpm		lb	kg	in	mm	dB(A)	cfm	l/s		
<b>0.7 hp (0.52 kw) - Lever Throttle - 200 Series Collet</b>											
SDG7S18F	18,000		1.2	0.6	6.0	150	81.8	25	12	1/4"	Front
SDG7S18M6F	18,000		1.2	0.6	6.0	150	81.8	25	12	6mm	Front
SDG7S25F	25,000		1.2	0.6	6.0	150	79.6	25	12	1/4"	Front
SDG7S25M6F	25,000		1.2	0.6	6.0	150	79.6	25	12	6mm	Front

**General:**

Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:**

Parts List • Safety and Instruction Manual • Collet & Wrenches



SAG7S15



**Right Angle Die Grinders**

Model Number	Free Speed		Weight		Length		Sound Level	Air Consumption Free Speed		Collet Size	Exhaust
	rpm		lb	kg	in	mm	dB(A)	cfm	l/s		
<b>0.70 hp (0.52 kw) - Lever Throttle - 200 Series Collet</b>											
SAG7S12	12,000		2.00	0.90	6.500	165	TBD	25	12	1/4"	Front
SAG7S12M6	12,000		2.00	0.90	6.500	165	TBD	25	12	6mm	Front
SAG7S15	15,000		2.00	0.90	6.500	165	TBD	25	12	1/4"	Front
SAG7S15M6	15,000		2.00	0.90	6.500	165	TBD	25	12	6mm	Front
SAG7S18	18,000		2.00	0.90	6.500	165	TBD	25	12	1/4"	Front
SAG7S18M6	18,000		2.00	0.90	6.500	165	TBD	25	12	6mm	Front

**General:**

Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:**

Parts List • Safety and Instruction Manual • Collet, Support Handle & Wrenches

siouxtools.com



250 Snap-on Drive  
P.O. Box 1596  
Murphy, North Carolina USA 28906  
PH: 828.835.9765  
FAX: 828.835.9685  
TOLL FREE: 866.259.7291  
TOLL FREE FAX: 800.722.7236

Benelux  
Tel: (N) +31-(0)880-104000  
(B) +32 (0)14-231967  
Fax: (N) +31-(0)880-104010  
(B) +32 (0)14-232627  
e-mail: (N) industrial.nl@snapon.com  
(B) industrial.be@snapon.com

Latin America  
Tel.: 305-271-0944  
Fax: 305-271-7152  
e-mail: latinamerica.caribbean@snapon.com

Germany  
Tel.: 49 2104 9509-0  
Fax: 49 2104 9509-99  
e-mail: indus.germany@snapon.com

Italy  
Tel.: 00 39 02 66 04 53 70  
Fax: 00 39 02 61 29 78 15  
e-mail: indus.italia@snapon.com

United Kingdom  
Tel.: 44 (0) 1536-413904  
Fax: 44 (0) 1536-413874  
e-mail: industrialuk@snapon.com

Asia  
Tel.: 65-6451-5570  
Fax: 65-6451-5574  
e-mail: esales.sg@snapon.com

Australia  
Tel.: 61 2 9837 9100  
Fax: 61 2 9624 2578  
e-mail:  
SOTA.customerservice@snapon.com

Distributed By:

