



SWG7AX SERIES EXTENDED ANGLE GRINDERS and SAG7AX SERIES EXTENDED ANGLE DIE GRINDERS



SWG7AX1345



SAG7AX20

Features:

- Powerful 5 vane motor maintains speed under load
- Robust aluminum motor housing
- Heavy duty double tapered collet
- Teasing throttle for maximum control
- Lever throttle with lock-off
- Ball bearing construction
- Heavy duty spiral bevel gearing for durability and smooth operation
- Compact steel angle head allows access into tight spaces
- Grease zerk in gear case
- Adjustable speed control



SAG7AX20

.7HP Extended Angle Die Grinders

Model Number	Free Speed	Weight		Length		Sound Level	Air Consumption		Collet Size	Spindle Thread	Exhaust
	rpm	lb	kg	in	mm	dB(A)	scfm	l/s			
SAG7AX13	13,300	2.9	1.3	10	254	TBD	25	12	1/4"	3/8" - 24	Front
SAG7AX13M6	13,300	2.9	1.3	10	254	TBD	25	12	6 mm	3/8" - 24	Front
SAG7AX16	16,000	2.9	1.3	10	254	TBD	25	12	1/4"	3/8" - 24	Front
SAG7AX16M6	16,000	2.9	1.3	10	254	TBD	25	12	6 mm	3/8" - 24	Front
SAG7AX20	20,000	2.9	1.3	10	254	TBD	25	12	1/4"	3/8" - 24	Front
SAG7AX20M6	20,000	2.9	1.3	10	254	TBD	25	12	6 mm	3/8" - 24	Front

General:

Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment:

Parts List • Safety and Instruction Manual • Collet & Wrenches



SWG7AX1345

.7HP Extended Angle Grinders

Model Number	Free Speed	Wheel Capacity		Weight		Length		Sound Level	Air Consumption		Spindle Thread	Exhaust
	rpm	in	mm	lb	kg	in	mm	dB(A)	scfm	l/s		
SWG7AX203	20,000	3	75	3.5	1.6	10	254	TBD	25	12	3/8" - 24	Front
SWG7AX134	13,300	4	100	3.5	1.6	10	254	87.4	25	12	3/8" - 24	Front
SWG7AX1345	13,300	4 1/2	115	3.5	1.6	10	254	88	25	12	5/8" - 11	Front

General:

Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment:

Parts List • Safety and Instruction Manual • Wrenches

siouxtools.com



250 Snap-on Drive
P.O. Box 1596
Murphy, North Carolina USA 28906
PH: 828.835.9765
FAX: 828.835.9685
TOLL FREE: 866.259.7291
TOLL FREE FAX: 800.722.7236

Benelux
Tel: (N) +31-(0)880-104000
(B) +32 (0)14-231967
Fax: (N) +31-(0)880-104010
(B) +32 (0)14-232627
e-mail: (N) industrial.nl@snapon.com
(B) industrial.be@snapon.com

Latin America
Tel.: 305-271-0944
Fax: 305-271-7152
e-mail: latinamerica.caribbean@snapon.com

Germany
Tel.: 49 2104 9509-0
Fax: 49 2104 9509-99
e-mail: indus.germany@snapon.com

Italy
Tel.: 00 39 02 66 04 53 70
Fax: 00 39 02 61 29 78 15
e-mail: indus.italia@snapon.com

United Kingdom
Tel.: 44 (0) 1536-413904
Fax: 44 (0) 1536-413874
e-mail: industrialuk@snapon.com

Asia
Tel.: 65-6451-5570
Fax: 65-6451-5574
e-mail: esales.sg@snapon.com

Australia
Tel.: 61 2 9837 9100
Fax: 61 2 9624 2578
e-mail:
SOTA.customerservice@snapon.com



Distributed By:

