



# NEW 1/2" LONG ANVIL IMPACT WRENCH



**IW500MP-4R3**

**Features:**

- 3" Long Anvil
  - Reach without Power Loss from the Extension
  - Flip Sockets
- Also Available in Pin Retainer



**IW500MP-BOOT**

*Fits all IW500MPs!*



**1/2" (13mm) Impact Wrenches**

Model Number	Drive Size		Bolt Cap Grade 5		Working Torque Range <sup>1</sup>		Maximum Torque		Blows Per Minute	Free Speed	Weight		Length		Side To Center		Avg Air Consumption		Socket Retainer Style
	in	mm	in	mm	ft lb	Nm	ft lb	Nm			lb	kg	in	mm	in	mm	cfm	l/s	
IW500MP-4R3	1/2	13	5/8	10	100-625	135-845	780	1058	1200	9400	4.4	2	10	254	1.5	38	4	2	Ring
IW500MP-4P3	1/2	13	5/8	10	100-625	135-845	780	1058	1200	9400	4.4	2	10	254	1.5	38	4	2	Pin

<sup>1</sup> Maximum working torque determined by 5 second rundown on appropriate Skidmore-Wilhelm Torque-Tension Tester.

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**Standard Equipment:** Parts List • Safety and Instruction Manual • Suspension Bail

**siouxtools.com**



250 Snap-on Drive  
P.O. Box 1596  
Murphy, North Carolina USA 28906  
PH: 828.835.9765  
FAX: 828.835.9685  
TOLL FREE: 866.259.7291  
TOLL FREE FAX: 800.722.7236

**Benelux**  
Tel: (N) +31-(0)880-104000  
(B) +32 (0)14-231967  
Fax: (N) +31-(0)880-104010  
(B) +32 (0)14-232627  
e-mail: (N) industrial.nl@snapon.com  
(B) industrial.be@snapon.com

**Latin America**  
Tel.: 305-271-0944  
Fax: 305-271-7152  
e-mail: latinamerica.caribbean@snapon.com

**Germany**  
Tel.: 49 2104 9509-0  
Fax: 49 2104 9509-99  
e-mail: indus.germany@snapon.com

**Italy**  
Tel.: 00 39 02 66 04 53 70  
Fax: 00 39 02 61 29 78 15  
e-mail: indus.italia@snapon.com

**United Kingdom**  
Tel.: 44 (0) 1536-413904  
Fax: 44 (0) 1536-413874  
e-mail: industrialuk@snapon.com

**Asia**  
Tel.: 65-6451-5570  
Fax: 65-6451-5574  
e-mail: esales.sg@snapon.com

**Australia**  
Tel.: 61 2 9837 9100  
Fax: 61 2 9624 2578  
e-mail: SOTA.customerservice@snapon.com