



SSD4P COMPACT PISTOL SCREWDRIVERS

0.4 hp Compact Screwdrivers



Adjustable Clutch



Positive Clutch



Stall Drive

Features:

- 0.4 HP – High Power to Weight Ratio
- 1-Hand Shuttle Reverse
- 3 Planet Gear-Set – Long Life
- Ergonomic Features:
 - Integrated Finger Rest
 - Contoured 3-Finger Grip
 - Low Noise
- Drop-In Motors – Ease of Service

SSD4P COMPACT PISTOL SCREWDRIVERS

Stall Pistol Grip

Model Number	Max. Torque (soft joint)		Free Speed rpm	Weight		Length		Side To Center		Maximum Air Consumption	
	in lb	Nm		lb	kg	in	mm	in	mm	cfm	l/s
0.4 hp (0.3 kw) Trigger Start - Shuttle Reverse											
SSD4P5S	95	10.7	500	1.5	0.7	5.5	140	0.7	17	20	10
SSD4P7S	65	7.3	700	1.5	0.7	5.5	140	0.7	17	20	10
SSD4P11S	45	5.1	1100	1.5	0.7	5.5	140	0.7	17	20	10
SSD4P14S	35	3.9	1400	1.3	0.6	5.0	127	0.7	17	20	10
SSD4P18S	26	2.9	1800	1.3	0.6	5.0	127	0.7	17	20	10
SSD4P26S	20	2.3	2600	1.3	0.6	5.0	127	0.7	17	20	10

Positive-Clutch Pistol Grip

Model Number	Max. Torque (soft joint)		Free Speed rpm	Weight		Length		Side To Center		Maximum Air Consumption	
	in lb	Nm		lb	kg	in	mm	in	mm	cfm	l/s
0.4 hp (0.3 kw) Trigger Start - Shuttle Reverse											
SSD4P5P	95	10.7	500	1.8	0.8	7.0	178	0.7	17	20	10
SSD4P7P	65	7.3	700	1.8	0.8	7.0	178	0.7	17	20	10
SSD4P11P	45	5.1	1100	1.8	0.8	7.0	178	0.7	17	20	10
SSD4P14P	35	3.9	1400	1.6	0.7	6.5	165	0.7	17	20	10
SSD4P18P	26	2.9	1800	1.6	0.7	6.5	165	0.7	17	20	10
SSD4P26P	20	2.3	2600	1.6	0.7	6.5	165	0.7	17	20	10

Adjustable-Clutch Pistol Grip

Model Number	Max. Torque (soft joint)		Free Speed rpm	Weight		Length		Side To Center		Maximum Air Consumption	
	in lb	Nm		lb	kg	in	mm	in	mm	cfm	l/s
0.4 hp (0.3 kw) Trigger Start - Shuttle Reverse											
SSD4P5AC	60	6.8	500	2.1	1.0	8.5	216	0.7	17	20	10
SSD4P7AC	60	6.8	700	2.1	1.0	8.5	216	0.7	17	20	10
SSD4P11AC	40	4.5	1100	2.1	1.0	8.5	216	0.7	17	20	10
SSD4P14AC	30	3.4	1400	1.9	0.9	8.0	203	0.7	17	20	10
SSD4P18AC	23	2.6	1800	1.9	0.9	8.0	203	0.7	17	20	10
SSD4P26AC	17	1.9	2600	1.9	0.9	8.0	203	0.7	17	20	10

siouxtools.com



250 Snap-on Drive
P.O. Box 1596
Murphy, North Carolina USA 28906
PH: 828.835.9765
FAX: 828.835.9685
TOLL FREE: 866.259.7291
TOLL FREE FAX: 800.722.7236

Belgium
Tel.: 32 (0)14 23 19 67
Fax: 32 (0)14 23 26 27
Email: Industrial.be@snapon.com

Netherlands
Tel.: 31 (0)88 0104000
Fax: 31 (0)88 0104010
Email: Industrial.nl@snapon.com

Latin America
Tel.: 786-254-7765
Fax: 786-534-9350
e-mail: latinamerica.caribbean@snapon.com

Germany
Tel.: 49 2104 9509-0
Fax: 49 2104 9509-99
e-mail: indus.germany@snapon.com

Italy
Tel.: 00 39 02 66 04 53 70
Fax: 00 39 02 61 29 78 15
e-mail: indus.italia@snapon.com

United Kingdom
Tel.: 44 (0) 1536-413904
Fax: 44 (0) 1536-413874
e-mail: industrialuk@snapon.com

Asia
Tel.: 65-6451-5570
Fax: 65-6451-5574
e-mail: esales.sg@snapon.com

Australia
Tel.: 61 2 9837 9100
Fax: 61 2 9624 2578
e-mail: SOTA.customerservice@snapon.com



Distributed By:

