



ANGLE SANDERS

High Power - Rugged Duty

2.2 hp



AS22S847



AS16S847

1.6 hp



Features and Benefits:

- High Power-to-Weight
- Governed Motor
- Low Profile Head
- Hex in Spindle
- Rotatable Exhaust
- Comfort Side Handle
- Guard Optional on 1.6 hp, 7"

ANGLE SANDERS



Angle Sanders



Model Number	Free Speed	Diameter		Weight		Length		Air Consumption Under Load		Air Consumption Free Speed	
	rpm	in	mm	lb	kg	in	mm	cfm	l/s	cfm	l/s
1.6 hp (1.2 kW) Angle Sanders											
AS16S125	12000	5	125	3.8	1.7	11.0	280	41	19	33	16
AS16S847	8400	7	175	3.8	1.7	11.0	280	41	19	33	16
1.6 hp (1.2 kW) Angle Sander with Guard											
AS16SG847	8400	7	175	4.5	2.0	11.0	280	41	19	33	16
2.2 hp (1.6 kW) Angle Sander											
AS22S847	8400	7	175	6.1	2.8	12.4	3.5	56	26	37	17



General: Air Inlet Size: 3/8" NPT • Recommended Hose Size: 1/2" (13 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Parts List • Safety and Instruction Manual • Spindle Wrenches • Backer Pad • Sanding Guard (AS16SG847)

siouxtools.com



250 Snap-on Drive
P.O. Box 1596
Murphy, North Carolina USA 28906
PH: 828.835.9765
FAX: 828.835.9685
TOLL FREE: 866.259.7291
TOLL FREE FAX: 800.722.7236

Belgium
Tel.: 32 (0)14 23 19 67
Fax: 32 (0)14 23 26 27
Email: Industrial.be@snapon.com

Netherlands
Tel.: 31 (0)88 0104000
Fax: 31 (0)88 0104010
Email: Industrial.nl@snapon.com

Latin America
Tel.: 786-254-7765
Fax: 786-534-9350
e-mail: latinamerica.caribbean@snapon.com

Germany
Tel.: 49 2104 9509-0
Fax: 49 2104 9509-99
e-mail: indus.germany@snapon.com

Italy
Tel.: 00 39 02 66 04 53 70
Fax: 00 39 02 61 29 78 15
e-mail: indus.italia@snapon.com

United Kingdom
Tel.: 44 (0) 1536-413904
Fax: 44 (0) 1536-413874
e-mail: industrialuk@snapon.com

Asia
Tel.: 65-6451-5570
Fax: 65-6451-5574
e-mail: esales.sg@snapon.com

Australia
Tel.: 61 2 9837 9100
Fax: 61 2 9624 2578
e-mail: SOTA.customerservice@snapon.com