



# TORQUE CONTROL SCREWDRIVERS

## Shut Off Clutch Screwdrivers



**SSD4P22TCRR**

### Features:

- Push to Start
- Shuts Off When Reaches Torque
- #1 Phillips Clutch Adjustment
- Rapid-Reverse – Momentary or Twist-Lock Reverse
- 0.4 hp in Compact Size
- Ergonomic Grip and Finger Rest
- Ease of Service



Model Number	Torque Range		Free Speed	Weight		Length		Side To Center		Air Consumption Free Speed	
	in lb	Nm	rpm	lb	kg	in	mm	in	mm	scfm	l/s
<b>0.4 hp (0.3 kw) Push to Start - Rapid Reverse</b>											
SSD4P5TCRR	5-60	0.6-6.8	500	2.2	1.0	8.7	220	0.7	20	20	9
SSD4P11TCRR	5-40	0.6-4.5	1100	2.2	1.0	8.7	220	0.7	20	20	9
SSD4P22TCRR	5-20	0.6-2.3	2200	1.9	0.9	8.2	210	0.7	20	20	9

Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

**siouxtools.com**



250 Snap-on Drive  
P.O. Box 1596  
Murphy, North Carolina USA 28906  
PH: 828.835.9765  
FAX: 828.835.9685  
TOLL FREE: 866.259.7291  
TOLL FREE FAX: 800.722.7236

Belgium  
Tel.: 32 (0)14 23 19 67  
Fax: 32 (0)14 23 26 27  
Email: Industrial.be@snapon.com

Netherlands  
Tel.: 31 (0)88 0104000  
Fax: 31 (0)88 0104010  
Email: Industrial.nl@snapon.com

Latin America  
Tel.: 786-254-7765  
Fax: 786-534-9350  
e-mail: latinamerica.caribbean@snapon.com

Germany  
Tel.: 49 2104 9509-0  
Fax: 49 2104 9509-99  
e-mail: indus.germany@snapon.com

Italy  
Tel.: 00 39 02 66 04 53 70  
Fax: 00 39 02 61 29 78 15  
e-mail: indus.italia@snapon.com

United Kingdom  
Tel.: 44 (0) 1536-413904  
Fax: 44 (0) 1536-413874  
e-mail: industrialuk@snapon.com

Asia  
Tel.: 65-6451-5570  
Fax: 65-6451-5574  
e-mail: esales.sg@snapon.com

Australia  
Tel.: 61 2 9837 9100  
Fax: 61 2 9624 2578  
e-mail:  
SOTA.customerservice@snapon.com